

Snap-In Miniature Bi-Pin Fluorescent Lamp Lampholders

APPLICATION and PERFORMANCE SPECIFICATION

Description: Non-Shunted Lampholders for T5 lamps

- Lampholder Material PBT GF
- Quick connect terminals: 18 AWG Solid and Stranded

- 120W / 600V
- IEC Temperature Rating T140

Type	Ref. #	Lamp Axis (mm)	Mounting Type	Mounting	Drawing	Weight (g)	Packing Unit
09440	505747	14	Snap In	19.5 x 9.7	A	3.3	1000
09446	545894	18	Snap In	19.5 x 9.7	B	3.5	1000
09447	545896	23	Snap In	19.5 x 9.7	C	3.8	1000
09450	505750	15	Snap In W/Pins	Ø3.7mm 13.2mm OC	D	3.4	1000
09460	505751	11.8	Snap In W/Pins	Ø3.2mm 19.5mm OC	E	3.1	1000
09465	508314	11.8	Snap In W/Pins	Ø3.2mm 18mm	F	3.1	1000

Physical Parameters

- For wall thickness from 0.024" - 0.039"
- Please see drawings

Safety:






- cULUS listed - Indoor Use (E110363)
- VDE/ENEC Approved

Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60838
- Lampholders meet IP20 standard

Warranty:




Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.






Drawing A

Drawing B




Drawing C



Drawing D



Drawing E



Drawing F

