

Flush-Mount Medium Bi-Pin Fluorescent Lamp Lampholders

APPLICATION and PERFORMANCE SPECIFICATION

Description: Flush mount big rotor lampholders for T8/T12 Lamps

- **Body:** PC Rotor PBT GF
- Base or lateral push-in terminals: 18AWG
- Laterl fixing clips for wall thickness 0.4-2mm
- 660W/600V
- IEC rating to T130

Type	Ref. #	Lamp Axis	Mounting	Starter Holder	Drawing	Weight (g)	Packing Unit
27356	100551	17	Mounting foot for #6 screws	-	A	5.4	1000 pcs
27722	100572	25.5	3.8mm mounting hole	-	B	7	500 pcs
27822	100583	25.5	3.8mm mounting hole	X	C	9	500 pcs

Safety:

- cUL_{US} listed - Indoor Use (E110363)
- ENEC



Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60400
- Lampholders meet IP20 standard except were otherwise noted

Warranty:

Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.

