

# LED Power Supply Product Specifications

LF1048 Series Switch-Mode LED Driver	
Total Power	53 Watts max.
Input Voltages	100-277 VAC
Number of Outputs	Single

ANZ#: Z155C, September 7, 2011

## SPECIAL FEATURES

- Single output 53-watts max. (selective models)
- In compliance to EN61000-3-2, -3-3 Class D
- Low Inrush Current maximize number of hookup
- Compatible with 0-10V dimming devices (current-source or current-drain)
- Available with C/C or C/V mode
- Suitable for dry and damp location applications
- OCP, OVP, OPP and SCP – shut down  
OTP – Auto-recovery

## ELECTRICAL SPECIFICATIONS

Input range	100 to 277 VAC/0.8-0.4A , Full range
Frequency	47 to 63 Hz
Power Factor	> 0.92 at 50%~100% load, 115 and 230VAC
THD	Less than 20%
Inrush current	< 35.0A/115Vac or <70A/230Vac, cold start, 25° C
Efficiency	15V/83%, 24V/85%, 48V/87%, 115Vac full load
EMI filtering	47CFR, Part 2, Part 15 and Cispr PUB, 22 Class B
Maximum power	53 Watts
Line Regulation	3%
Load Regulation	±5%
Ripple Noise	1% typ.
Leakage Current	<0.75mA @ 230VAC
Surge Immunity	4K VAC
Protection	Over-voltage, Over-current, Over-temp. and Short circuit protection

## ENVIRONMENTAL

Operating temperature:	-30 to 70 °C (De-rating : 2.5% per °C from 50°C~70°C )
Storage temperature:	-40 to 85 °C
Humidity (Non-Condensing):	5% to 95%
Cooling:	Convection
Vibration Frequency:	5 to 50 Hz
MTBF:	>100,000 Hours at full load and 25°C ambient conditions (MIL-217F)
EMC :	Compliant to 47CFR, Part 2, Part15 and Cispr PUB, 22 Class B
Acoustic Noise:	Less than 24db (20~20K Hz)

## SAFETY

UL/cUL	UL8750 Recognized
CE	Certified (EN55015, EN61547, EN61347, EN61000-3-2 D)

## MODEL SELECTION

Model	Constant Voltage Models			Constant Current Models		Max. Output (Watt)
	Output Volts	V-Adj. (±5%)	I-out (min./max)	I-Adj. (±5%)	Voltage (Vf)	
LF1048-15	15V(12V)	9 ~ 16.5V	280 ~2800/3500mA	1400 ~2800/3500mA	8 ~ 16.5V(12V)	42
LF1048-24	24V(20V)	15 ~26.4V	200 ~2000/2400mA	1000 ~2000/2400mA	12 ~26.4V(20V)	48
LF1048-36	36V(28V)	24 ~39.6V	150 ~1350/1700mA	700 ~1350/1700mA	18 ~39.6V(28V)	48
LF1048-48	48V(40V)	36 ~52.8V	100 ~1000/1200mA	500 ~1000/1200mA	30 ~ 52.8V(40V)	48
LF1048-88	N/A			300 ~750mA	40 ~ 88V	53
LF1048-160	N/A			200 ~ 420mA	60 ~ 160V	53

## MECHANICAL DRAWING

### Model Information – LF1048-XX-Cnnnn-DDDD, single DC output, 48 – 53W total

XX – Voltage range, 15=15V, 24=24V, 48=48V etc....

Cnnnn – (Optional or Blank) Constant Current Output, C3500=3500mA, C2200=2200mA etc.....

DDDD – (Optional or Blank)

-1631 = On/Off AC Step dimming, T1:100%, T2:60%, T3:35%, T4:15% (timing 1.5 Sec. between steps)

-010V = 1-10V dimming control or use 10-100KΩ variable resistor

