



66915 - LED 25 DC 12V PUS

GELD25DMV12PUS

- Previous SKU: 901025012PUS
- 25W DC 12V constant voltage LED driver. Aluminum Casing. White color prevents shadowing in signage applications. Potted.
- Current: DC

GENERAL CHARACTERISTICS

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	75 °C
Storage Temperature	-10 °C
Color	White
Product Technology	LED
CV/CC	CV
CC/CVValue	12 V
Output Power (W)	25 W
Output Current (A)	2 A
Output Voltage[Nom]	12 V

PRODUCT INFORMATION

Product Code	66915
Description	GELD25DMV12PUS
Alternative Unit Of Measure	EACH
Standard Package Quantity	24
Ean UPC	043168669153
Standard Package GTIN	00043168669153
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	24
Sales Unit	Each
UCC	043168669153
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168669153
Standard Package GTIN	10043168669150
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168669153

ELECTRICAL CHARACTERISTICS

Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	60 Hz
Input Current Range[Min]	0.3 A
Input Voltage Range[Min] (V)	0.1 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	277
Input voltage Range	V V