

66884 - LED 18W DC 700mA Aluminum

GELD18DMV700PU 120

- ☞ Previous SKU: 901018700PU
- ☞ LED 18W DC 700mA - LED Driver, Constant Current, Aluminum Housing, Potted, with Leads
- ☞ Current: DC
- ☞ Dimmable with Trailing Edge dimmers
- ☞ IP67
- ☞ Reinforced insulation from input to output
- ☞ High efficiency
- ☞ PFC: > 0.95 Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch, Overload regulation, Over voltage protection, Self-resetting
- ☞ AC/DC
- ☞ Soft start

GENERAL CHARACTERISTICS

Enclosure Type	Metal
Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Color	Black
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambience lighting
Product Technology	LED
Rated Life Hours-nominal	0 h
CV/CC	CC
CC/CVValue	700 mA
Output Power (W)	18 W
Output Current (A)	0.7 A
Output Voltage[Min]	4 V
Output Voltage[Max]	26 V
Output Voltage[Nom]	120 V

PRODUCT INFORMATION

Product Code	66884
Description	GELD18DMV700PU 120
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168668842
Standard Package GTIN	00043168668842
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168668842
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168668842
Standard Package GTIN	10043168668849
No Of Items Per Sales Unit	
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	043168668842

ELECTRICAL CHARACTERISTICS

Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.17 A
Input Voltage Range[Min] (V)	0.09 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	277
Input voltage Range	V V
Rated power (Watts)	0 W