

66872 - LED 18W 350mA Bottom Feed

GELD18DMV350BF 120

- ☞ Previous SKU: 901018350BF
- ☞ 18W DC 350mA constant current LED driver. From 1 to 15 LEDs in a series. Aluminum Casing. Potted. Bottom Feed. USA version.
- ☞ Current: DC
- ☞ Dimmable with Trailing Edge dimmers
- ☞ Designed for IP67
- ☞ Reinforced insulation from input to output
- ☞ High efficiency
- ☞ PFC: > 0.95 Fully protected: Short circuit, Input voltage surge, Thermal, Secondary switch Overload regulation, Over voltage protection. Self-resettable
- ☞ AC/DC

GENERAL CHARACTERISTICS

Ambient Temp [Max]	50 °C
Ambient Temp [Min]	-25 °C
Case Temperature (Max)	80 °C
Storage Temperature	-10 °C
Primary Application	LED in- and outdoor lighting Street lighting Architectural lighting Sigge Indication and orientation lighting Ambience lighting
Product Technology	LED
Rated Life Hours-nominal	0 h
CV/CC	CC
CC/CVValue	350 mA
Output Power (W)	18 W
Output Current (A)	0.35 A
Output Voltage[Min]	4 V
Output Voltage[Max]	52 V
Output Voltage[Nom]	120 V

PRODUCT INFORMATION

Product Code	66872
Description	GELD18DMV350BF 120
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168668729
Standard Package GTIN	00043168668729
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	043168668729
Alternative Unit Of Measure	CASE
Standard Package Quantity	0
Ean UPC	043168668729
Standard Package GTIN	10043168668726
No Of Items Per Sales Unit	0
No Of Items Per Standard Package	0
Sales Unit	Case
UCC	043168668729

ELECTRICAL CHARACTERISTICS

Outrush Current (Milliamperes)	0 kHz
Input Current Range[Max]	50 Hz
Input Current Range[Min]	0.17 A
Input Voltage Range[Min] (V)	0.09 A
Input Voltage Range[Max]	120 V
Input Current Range (Amperes)	277
Input voltage Range	V V
Rated power (Watts)	0 W