

Miniature Bi Pin (G5) Butt-On Lampholders

APPLICATION and PERFORMANCE SPECIFICATION

Description: Butt-On Lampholders for T5 lamps

- Lampholder Material PBT GF
- Quick connect terminals: 18 AWG Solid and Stranded
- 120W / 600V
- IEC Temperature Rating T140

Type	Ref. #	Pin Orientation	W/Spring	Shunted	Drawing	Weight (g)	Packing Unit
09404	505732	Lateral Clips	-	-	A	2.8	1000 pcs
09804	508261	Lateral Clips	-	X	A	2.8	1000 pcs
09405	505733	Horizontal Pins	-	-	B	2.9	1000 pcs
09805	508262	Horizontal Pins	-	X	B	2.9	1000 pcs
09406	505734	Horizontal Pins	X	-	B	3.3	1000 pcs
09806	508263	Horizontal Pins	X	X	B	3.3	1000 pcs
09407	508590	Horizontal Pins	-	-	C	3	1000 pcs
09807	520739	Horizontal Pins	-	X	C	3	1000 pcs
09415	505735	Vertical Pins	-	-	D	2.9	1000 pcs
09815	508264	Vertical Pins	-	X	D	2.9	1000 pcs
09416	505736	Vertical Pins	X	-	D	3.2	1000 pcs
09816	508265	Vertical Pins	X	X	D	3.2	1000 pcs

* Foot: PC Body and Rotor: PBT

Physical Parameters

- For wall thickness from 0.020" - 0.059"
- Please see drawings

Performance:

- Meets ANSI Standard C81.62-2009
- Meets IEC Standard 60400
- Lampholders meet IP20 standard

Safety:

- cUL_{US} listed - Indoor Use (E110363)
- VDE/ENEC Approved



Warranty:

Universal Lighting Technologies warrants to the purchaser that each lampholder will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. Call **1-800-BALLASTx800** for technical assistance.








Figure A

Figure C













Figure B

Figure D